

QAHV

Monobloc Air Source Heat Pump

ecodan[®]
Renewable Heating Technology

A Highly Efficient, Carbon Saving Solution for Commercial Sanitary Hot Water Production



QAHV Monobloc Air Source Heat Pump

Specifically designed for commercial sanitary hot water application, where gas boilers, combined heat and power systems (CHP) or electric water heating have been traditionally utilised, the QAHV provides a low carbon solution for hospitals, hotels, leisure centres and student accommodation.

Utilising the natural and stable refrigerant CO₂ (R744), the environmentally clean solution enables compliance to strict local planning laws and boosts BREEAM points. Compounded by the increasing decarbonisation of the electrical grid and the UK's commitment to Net Zero 2050, the QAHV provides a high efficiency, low carbon hot water delivery solution with leaving water temperature up to 90°C.



High efficiency
at high flow
temperatures



Utilises CO₂
refrigerant with
a GWP of 1



Uses a unique twisted
and spiral gas cooler
to enhance energy
efficiency



Full heating capacity
down to -3°C outdoor
temperature and
operates down to -25°C





Super low
noise levels



Patented Technology

QAHV utilises a unique twisted and spiral gas cooler, the 3 connected refrigerant pipes are wound around the twisted water pipe which maximizes heat transfer.


The continuous spiral grooves in the twisted pipe accelerates the turbulence effect of water and also helps to reduce pressure loss within the heat exchanger which contribute to enhance efficiency. Equipped with the latest inverter scroll compressor, QAHV can significantly increase the annual efficiency.




High Performance

High efficiency levels provide significant savings in running costs and carbon emissions against direct electric heating systems.

QAHV is able to provide full heating capacity even at ambient temperatures of -3°C . Furthermore, the unit can supply hot water in ambient temperatures as low as -25°C .




The technology behind this is an injection circuit which provides optimum amount of refrigerant to the system via a compressor through a specially designed injection port to ensure a particularly stable operation.



Healthcare



Hotels



QAHV is ideal for applications with demand for
Low Carbon High Temperature Hot Water


Leisure



Student Accommodation



With an M-NET ready connection, the QAHV solution can be controlled alongside Mitsubishi Electric's City Multi, Mr Slim, e-Series Chillers and others.





OUTDOOR UNIT		QAHV-N560YA-HPB	
WATER HEATING 65°C ¹	CAPACITY (kW)	40	
	POWER INPUT (kW)	10.31	
	CURRENT INPUT (A)	16.3	
	COP	3.88	
WATER HEATING 65°C ²	CAPACITY (kW)	40	
	POWER INPUT (kW)	10.97	
	CURRENT INPUT (A)	18.3	
	COP	3.65	
WATER HEATING 65°C ³	CAPACITY (kW)	40	
	POWER INPUT (kW)	11.6	
	CURRENT INPUT (A)	18.7	
	COP	3.44	
WATER HEATING ENERGY EFFICIENCY CLASS	FOR MEDIUM TEMPERATURE APPLICATION	A	
	INLET WATER TEMPERATURE (°C)	5 ~ 63	
	OUTLET WATER TEMPERATURE (°C)	55 ~ 90	
	OUTDOOR TEMPERATURE (°C)	-25 ~ -43	
ELECTRICAL	MAX CURRENT INPUT (A)	33.8	
	ELECTRICAL SUPPLY (V / Hz)	380-415v, 50Hz	
	PHASE	3	
	FUSE RATING - MCB SIZES (A) ⁵	40	
WATER DETAIL	INLET / OUTLET (mm (in.))	19.05 (Rc 3/4"), screw pipe / 19.05 (Rc 3/4"), screw pipe	
	ALLOWABLE EXTERNAL PUMP HEAD (kPa)	77	
DIMENSIONS (mm)	WIDTH	1220	
	DEPTH	760	
	HEIGHT	1837 (1777 without legs)	
WEIGHT (kg)		400	
NOISE LEVEL	SOUND PRESSURE ⁴ (dB(A))	56	
REFRIGERANT	TYPE	R744 (GWP 1)	
	REFRIGERANT CHARGE (kg) / CO ₂ EQUIVALENT (t)	6.5 / 0.0065	


Notes: *1 Under Normal heating conditions at the outdoor temp, 16°CDB/12°CWB, the outlet water temperature 65°C, and the inlet water temperature 17°C.

*2 Under Normal heating conditions at the outdoor temp, 7°CDB/6°CWB, the outlet water temperature 65°C, and the inlet water temperature 9°C.


*3 Under Normal heating conditions at the outdoor temp, 7°CDB/6°CWB, the outlet water temperature 65°C, and the inlet water temperature 15°C.

*4 Measured 1m from the front of the unit in an anechoic room. *5 MCB Sizes BS EN60898-2 & BS EN60947-2

QAHV-N560YA-HPB DIMENSIONS



Telephone: 01707 282880
email: air.conditioning@meuk.mee.co.uk
les.mitsubishielectric.co.uk



UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division, Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England. Telephone: 01707 282880 Fax: 01707 278881
IRELAND Mitsubishi Electric Europe, Westgate Business Park, Ballymount, Dublin 24, Ireland. Telephone: (01) 419 8800 Fax: (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2020. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Notes: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP:2088), R32 (GWP:675), R407C (GWP:1774) or R134a (GWP:1430). *These GWP values are based on Regulation (EU) No 517/2014 from IPCC 4th edition. In case of Regulation (EU) No.626/2011 from IPCC 3rd edition, these are as follows. R410A (GWP:1975), R32 (GWP:550), R407C (GWP:1650) or R134a (GWP:1300).

Effective as of May 2020

