



- Stone Schedule for information**
W01/02
 SOLID STAGGERED UNITS:
 Solid stone units with 25mm radius to top edges. Recess to match shadow gap as adjacent cladding/coping units.
 Rubbed finish.
 4 no. 300 x 500 x 310mm high (TYPE F) sitting on 2 x 215mm courses blockwork
 15 no. 300 x 500 x 525mm high (TYPE G) sitting on 1 x 215mm courses blockwork
 8 no. 300 x 500 x 740 high (Type I)
 1 no. tapered 454 x 500 x 740 high (TYPE H1)
 1 no. corner special 740 high (Type H2)
 Units to be fabricated either as one piece or in two pieces (coping separate)

COPIING:
125 x 400 x 500 mm with 25 mm radius edge and anti-skate detail as drawing **252194-LPP-95-SW-L00-L0401**.
Predrilled for stainless steel dowels into wall construction below.
14 no. 500mm long units with skate recess as drawing **252194-LPP-95-SW-L00-DET-L0401**, (TYPE C)
15 no. 500mm long units without recess (TYPE D1)

CLADDING:
40mm thick yorkstone cladding as **F21/120** with fixings by Ancon as **F30/10** to blockwork construction.
500mm wide panels: 29 no. @ 615mm high (TYPE J)
556mm wide panels: 1 no. @ 615mm high

Dimensions do not include for joints - to be advised by fabricator.

© All information contained within this document remains copyright of Landscape Projects Ltd. and shall not be reproduced without prior consent.

(1) Do not scale from drawings - use written dimensions only. (2) All dimensions are in millimeters unless noted. (3) All dimensions shall be verified on site before proceeding with the work. (4) Landscape Projects shall be notified of any discrepancies. (5) Engineer to specify all sub-bases. Any below ground construction is indicative.

landscape projects

Landscape Architecture & Design
31 Blackfriars Road Salford Manchester M3 7AQ
PHONE: 0161 839 8336 FAX: 0161 839 7155
EMAIL: post@landscapeprojects.co.uk