



THIS DRAWING IS COPYRIGHT PROTECTED AND MAY NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN AUTHORITY FROM THE OWNER.

- NOTES:**
1. Do not scale from this drawing.
 2. Always work to noted dimensions.
 3. All dimensions are in millimetres unless otherwise stated.
 4. All setting out, levels and dimensions to be agreed on site.
 5. The dimensions of all materials must be checked on site before being laid out.
 6. This drawing must be read with the relevant specification clauses and detail drawings.
 7. Order of construction and setting out to be agreed on site.

HARDWORKS

- H1 PERFECTA PAVING**
Location: To Footpaths
Product: Marshalls 'Perfecta' or equal and approved
Size: 450 x 450 x 30mm
Laying: Stretchebond - Rigid Buildup
- H2 YORKSTONE PAVING**
Location: To Main Entrance to Building
Product: Marshalls 'Scoutmoor' or equal and approved
Size: 600 x 300 x 50mm
Laying: Stretchebond - Rigid Buildup
- H3 YORKSTONE SETTS**
Location: To Gravelly Row Pedestrian Crossing
Product: Marshalls 'Scoutmoor' or equal and approved
Size: 150 x 80 x 80mm
Laying: Stretchebond - Rigid Buildup
- H4 TEGULA SETTS**
Location: To Parking Bays on Gravelly Row
Product: Marshalls 'Tegula Cobblet' or equal and approved
Size: 80 x 80 x 40mm
Colour: Traditional
Laying: Stretchebond - Rigid Buildup
- H5 TEGULA SETTS**
Location: To demarcate parking bays + to hatched area of disabled bays
Product: Marshalls 'Tegula Cobblet' or equal and approved
Size: 80 x 80 x 40mm
Colour: Permanent Grey
Laying: Stretchebond - Rigid Buildup
- H6 HRA CARRIAGEWAY - TO BE RESURFACED**
- Existing surface to be planned off.
- Tack coat & New Blacktop HRA surface to be laid.
- To Engineer's Specification
- Re-lined as required to match existing highway arrangements.
- H7 GRAVEL STRIPE**
Location: To southern building facade interface
Product: CED Stone 'Budd Thames Gravel' or equal and approved
Colour: Buff
Size: 20mm
- B1 BLISTER PAVING**
Product: Granite or or equal and approved
Colour: 'Kobral' / Dark grey
Size: W: 200mm L: 200mm D: 50mm

- KERBS**
- K1 CONCRETE UPSTAND KERB K1**
- 125mm upstand PCC concrete kerbs
- K2 CONCRETE UPSTAND KERB K2**
- 50mm upstand PCC concrete kerbs
- K3 CONCRETE FLUSH KERB**
- Flush PCC concrete kerbs
- K4 CONCRETE DROP KERB**
- Drop PCC concrete kerbs
- PCC CONCRETE KERBS**
Specification: Various profiles
Standard concrete kerbs/ droppers/ transitions/ flush and radius units as required
Supplier: Marshalls site or equal approved
To engineers specification and layout
- K1** 125mm Upstand
K2 50mm Upstand
K3 Flush
K4 Drop Kerbs

INTERNAL & EXTERNAL KERB ANGLES TO BE USED ON ALL CORNERS

P05	27-04-23	Ramp updates	RM	RM
P04	13-04-23	Amends following building layout updates	YH	RM
P03	29-03-23	Dwg no. updates	YH	RM
P02	22-03-23	Updates following layout change	YH	RM
P01	02-03-23	Adopted from old drawing	YH	RM

Revision	Date	Description	Drawn	Apprvd.
----------	------	-------------	-------	---------

Plant I.E. Limited
Manchester | London | Liverpool | Leeds | Standish
E: info@plant-ie.com W: plant-ie.com

MANCHESTER
2 Back Grafton St.,
Altrincham,
WAL4 1DY
T: 0161 928 9281

Client IQ Student Accommodation

Project Echo Street, Manchester

Drg Title Externals HARDWORKS + EDGING

Created on 02-03-23
Created by YH
Approved by RM

Scale 1:200
Size A1
Workstage Comments

Drg No. PL1832-PLA-XX-ZZ-DR-L-1000
Suitability S3