



Simple to install and operate, this system automatically limits the sound output from pubs and clubs, thus avoiding costly prosecutions and closures. The system comes fitted with a 40A, 4-pole circuit breaker and the microphone unit can be fitted to any standard BS1363 backing box (85mm²).

The unit will continually monitor the sound levels and displays a green LED on the control unit at this time, the LED changes to amber when the level reaches 6dB below threshold and red at 3dB below threshold. At threshold, the contactor will be switched off and the red LED will flash, after the off time has elapsed the contactor will switch on again.

High Intensity LED Display

A remote LED indicator panel which fits directly to any 85mm square BS1363 backbox. The display replicates the display on the main panel with 7 green, 7 amber and 7 red high intensity LEDs.

Optional Volume Control

Automatic volume control to adjust the audio line level to amplification equipment if the output reaches the amber (-6dB) level. 2 Balanced line XLR inputs and outputs.

Audio Setting Levels	70dB to 110dB
Weighting	'A' or 'C' switchable
Amber Trigger	-6dB below threshold
Red Trigger	-3dB below threshold
Power	12V dc
Relay	4-pole 40A, will work as 3 Phase and Neutral, 4 single phase or 2 x single phase live and neutral

383770.335963

Description	Order Code	Price Each
Sound Limiter and Contact Breaker	868-7277 ▲	
LED Display	868-7285 ▲	
Volume Control	868-7293 ▲	