

- Brick Slips:
- All 102.5mm brickslips to be cut from standard brickslip length
 - Overall setting out dimension to be maintained via site adjustment of joints

- SFS:
- SFS position is indicative

- Tolerances:
- Window installation +/- 2mm
 - SHS installation +/-10mm

- Firestopping:
- No cavities to be allowed during insulation installation

Hazard Identification Legend

Hazard Identification (if none state 'None relevant')	Control and Mitigation Measures
None Assessed/Not Used	

Note:
Hazards listed above are only those considered significant risks and:

a) not likely to be obvious to a competent contractor or other designers;
b) unusual; or
c) likely to be difficult to manage effectively

C01	13-02-2023	For Construction	MB	DM	KL
P01	03-02-2023	For Review and Comment	BV	DM	KL
REV	DATE	DESCRIPTION	DWN	CHK	APP

Do not scale from this drawing. All dimensions to be verified on site prior to the commencement of any work or the production of any shop drawings. All discrepancies to be reported to Bryden Wood Ltd. This drawing is to be read in conjunction with all related Consultant's drawings and any other relevant information. This drawing is the copyright of Bryden Wood Ltd.

Key:

Project:
Victoria House

Drawing Title:
Facade - Typical Slab Edge Detail - Level 09
Cantilever Soffit to Cill

Drawing Number:
22017-BWT-ZZ-XX-DR-Y-0062

Scale:	Paper Size:	Status:	Revision:
1 : 5	A3	S3	C01

