

Junctions 9			
PICADY 9 - Priority Intersection Module			
Version: 9.5.1.7462			
© Copyright TRL Limited, 2019			
For sales and distribution information, program advice and maintenance, contact TRL:			
+44 (0)1344 379777 software@trl.co.uk www.trlsoftware.co.uk			
The users of this computer program for the solution of an engineering problem are in no way relieved of their responsibility for the correctness of the solution			

Filename: Site Access Model.j9

Path: C:\Users\DanielAckerley\Dynamic Transport Planning Limited\Dynamic Transport Planning Limited - Job Library\2022\3706122 - Cheetham Hill, Shirley Rd\5 - Traffic Data

Report generation date: 14/12/2022 10:10:21

- »2023 Base + Existing, AM
- »2023 Base + Existing, PM
- »2023 Base + Existing + Dev, AM
- »2023 Base + Existing + Dev, PM
- »2027 Base + Existing, AM
- »2027 Base + Existing, PM
- »2027 Base + Existing + Dev, AM
- »2027 Base + Existing + Dev, PM

Summary of junction performance

	AM				PM			
	Set ID	Queue (PCU)	RFC	LOS	Set ID	Queue (PCU)	RFC	LOS
	2023 Base + Existing							
Stream B-AC	D1	0.0	0.00	A	D2	0.0	0.00	A
Stream C-AB		0.1	0.05	A		0.1	0.07	A
	2023 Base + Existing + Dev							
Stream B-AC	D3	0.0	0.00	A	D4	0.0	0.00	A
Stream C-AB		0.1	0.10	A		0.1	0.07	A
	2027 Base + Existing							
Stream B-AC	D5	0.0	0.00	A	D6	0.0	0.00	A
Stream C-AB		0.1	0.05	A		0.1	0.07	A
	2027 Base + Existing + Dev							
Stream B-AC	D7	0.0	0.00	A	D8	0.0	0.00	A
Stream C-AB		0.1	0.10	A		0.1	0.07	A

Values shown are the highest values encountered over all time segments. Delay is the maximum value of average delay per arriving vehicle.

File summary

File Description

Title	Cheetham Hill Road - Site Access
Location	Manchester
Site number	1
Date	16/11/2022
Version	
Status	(new file)
Identifier	
Client	
Jobnumber	3706122
Enumerator	DTP
Description	

Units

Distance units	Speed units	Traffic units input	Traffic units results	Flow units	Average delay units	Total delay units	Rate of delay units
m	kph	PCU	PCU	perHour	s	-Min	perMin

Analysis Options

Calculate Queue Percentiles	Calculate residual capacity	RFC Threshold	Average Delay threshold (s)	Queue threshold (PCU)
		0.85	36.00	20.00

Demand Set Summary

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)
D1	2023 Base + Existing	AM	ONE HOUR	07:45	09:15	15
D2	2023 Base + Existing	PM	ONE HOUR	16:45	18:15	15
D3	2023 Base + Existing + Dev	AM	ONE HOUR	07:45	09:15	15
D4	2023 Base + Existing + Dev	PM	ONE HOUR	16:45	18:15	15
D5	2027 Base + Existing	AM	ONE HOUR	07:45	09:15	15
D6	2027 Base + Existing	PM	ONE HOUR	16:45	18:15	15
D7	2027 Base + Existing + Dev	AM	ONE HOUR	07:45	09:15	15
D8	2027 Base + Existing + Dev	PM	ONE HOUR	16:45	18:15	15

Analysis Set Details

ID	Network flow scaling factor (%)
A1	100.000

2023 Base + Existing, AM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	untitled	T-Junction	Two-way		0.14	A

Junction Network Options

Driving side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description	Arm type
A	Cheetham Hill Road W		Major
B	Site Access		Minor
C	Cheetham Hill Road E		Major

Major Arm Geometry

Arm	Width of carriageway (m)	Has kerbed central reserve	Has right turn bay	Visibility for right turn (m)	Blocks?	Blocking queue (PCU)
C	8.70			200.0	✓	1.00

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Minor Arm Geometry

Arm	Minor arm type	Lane width (m)	Visibility to left (m)	Visibility to right (m)
B	One lane	5.00	0	0

Slope / Intercept / Capacity

Priority Intersection Slopes and Intercepts

Stream	Intercept (PCU/hr)	Slope for A-B	Slope for A-C	Slope for C-A	Slope for C-B
B-A	574	0.092	0.233	0.147	0.333
B-C	749	0.101	0.256	-	-
C-B	690	0.236	0.236	-	-

The slopes and intercepts shown above do NOT include any corrections or adjustments.

Streams may be combined, in which case capacity will be adjusted.

Values are shown for the first time segment only; they may differ for subsequent time segments.

Traffic Demand

Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)
D1	2023 Base + Existing	AM	ONE HOUR	07:45	09:15	15

Default vehicle mix	Vehicle mix source	PCU Factor for a HV (PCU)
✓	HV Percentages	2.00

Demand overview (Traffic)

Arm	Linked arm	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		✓	707	100.000
B		✓	0	100.000
C		✓	472	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
		A	B	C
	A	0	17	690
	B	0	0	0
	C	451	21	0

Vehicle Mix

Heavy Vehicle Percentages

	To			
		A	B	C
	A	10	10	10
	B	10	10	10
	C	10	10	10

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS
B-AC	0.00	0.00	0.0	A
C-AB	0.05	7.74	0.1	A
C-A				
A-B				
A-C				

2023 Base + Existing, PM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	untitled	T-Junction	Two-way		0.25	A

Junction Network Options

Driving side	Lighting
Left	Normal/unknown

Traffic Demand

Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)
D2	2023 Base + Existing	PM	ONE HOUR	16:45	18:15	15

Default vehicle mix	Vehicle mix source	PCU Factor for a HV (PCU)
✓	HV Percentages	2.00

Demand overview (Traffic)

Arm	Linked arm	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		✓	555	100.000
B		✓	0	100.000
C		✓	513	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	35	520
	B	0	0	0
	C	478	35	0

Vehicle Mix

Heavy Vehicle Percentages

	To			
	A	B	C	
From	A	10	10	10
	B	10	10	10
	C	10	10	10

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS
B-AC	0.00	0.00	0.0	A
C-AB	0.07	7.19	0.1	A
C-A				
A-B				
A-C				

2023 Base + Existing + Dev, AM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	untitled	T-Junction	Two-way		0.31	A

Junction Network Options

Driving side	Lighting
Left	Normal/unknown

Traffic Demand

Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)
D3	2023 Base + Existing + Dev	AM	ONE HOUR	07:45	09:15	15

Default vehicle mix	Vehicle mix source	PCU Factor for a HV (PCU)
✓	HV Percentages	2.00

Demand overview (Traffic)

Arm	Linked arm	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		✓	719	100.000
B		✓	0	100.000
C		✓	508	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	37	682
	B	0	0	0
	C	463	45	0

Vehicle Mix

Heavy Vehicle Percentages

	To			
	A	B	C	
From	A	10	10	10
	B	10	10	10
	C	10	10	10

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS
B-AC	0.00	0.00	0.0	A
C-AB	0.10	7.78	0.1	A
C-A				
A-B				
A-C				

2023 Base + Existing + Dev, PM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	untitled	T-Junction	Two-way		0.25	A

Junction Network Options

Driving side	Lighting
Left	Normal/unknown

Traffic Demand

Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)
D4	2023 Base + Existing + Dev	PM	ONE HOUR	16:45	18:15	15

Default vehicle mix	Vehicle mix source	PCU Factor for a HV (PCU)
✓	HV Percentages	2.00

Demand overview (Traffic)

Arm	Linked arm	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		✓	555	100.000
B		✓	0	100.000
C		✓	515	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	35	520
	B	0	0	0
	C	480	35	0

Vehicle Mix

Heavy Vehicle Percentages

	To			
	A	B	C	
From	A	10	10	10
	B	10	10	10
	C	10	10	10

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS
B-AC	0.00	0.00	0.0	A
C-AB	0.07	7.19	0.1	A
C-A				
A-B				
A-C				

2027 Base + Existing, AM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	untitled	T-Junction	Two-way		0.14	A

Junction Network Options

Driving side	Lighting
Left	Normal/unknown

Traffic Demand

Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)
D5	2027 Base + Existing	AM	ONE HOUR	07:45	09:15	15

Default vehicle mix	Vehicle mix source	PCU Factor for a HV (PCU)
✓	HV Percentages	2.00

Demand overview (Traffic)

Arm	Linked arm	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		✓	738	100.000
B		✓	0	100.000
C		✓	493	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	17	721
	B	0	0	0
	C	472	21	0

Vehicle Mix

Heavy Vehicle Percentages

	To			
	A	B	C	
From	A	10	10	10
	B	10	10	10
	C	10	10	10

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS
B-AC	0.00	0.00	0.0	A
C-AB	0.05	7.83	0.1	A
C-A				
A-B				
A-C				

2027 Base + Existing, PM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	untitled	T-Junction	Two-way		0.24	A

Junction Network Options

Driving side	Lighting
Left	Normal/unknown

Traffic Demand

Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)
D6	2027 Base + Existing	PM	ONE HOUR	16:45	18:15	15

Default vehicle mix	Vehicle mix source	PCU Factor for a HV (PCU)
✓	HV Percentages	2.00

Demand overview (Traffic)

Arm	Linked arm	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		✓	578	100.000
B		✓	0	100.000
C		✓	534	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	35	543
	B	0	0	0
	C	499	35	0

Vehicle Mix

Heavy Vehicle Percentages

	To			
	A	B	C	
From	A	10	10	10
	B	10	10	10
	C	10	10	10

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS
B-AC	0.00	0.00	0.0	A
C-AB	0.07	7.23	0.1	A
C-A				
A-B				
A-C				

2027 Base + Existing + Dev, AM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	untitled	T-Junction	Two-way		0.30	A

Junction Network Options

Driving side	Lighting
Left	Normal/unknown

Traffic Demand

Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)
D7	2027 Base + Existing + Dev	AM	ONE HOUR	07:45	09:15	15

Default vehicle mix	Vehicle mix source	PCU Factor for a HV (PCU)
✓	HV Percentages	2.00

Demand overview (Traffic)

Arm	Linked arm	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		✓	750	100.000
B		✓	0	100.000
C		✓	529	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
		A	B	C
	From	A	B	C
		0	37	713
		0	0	0
		484	45	0

Vehicle Mix

Heavy Vehicle Percentages

	To			
		A	B	C
	From	A	B	C
		10	10	10
		10	10	10
		10	10	10

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS
B-AC	0.00	0.00	0.0	A
C-AB	0.10	7.85	0.1	A
C-A				
A-B				
A-C				

2027 Base + Existing + Dev, PM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	untitled	T-Junction	Two-way		0.24	A

Junction Network Options

Driving side	Lighting
Left	Normal/unknown

Traffic Demand

Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)
D8	2027 Base + Existing + Dev	PM	ONE HOUR	16:45	18:15	15

Default vehicle mix	Vehicle mix source	PCU Factor for a HV (PCU)
✓	HV Percentages	2.00

Demand overview (Traffic)

Arm	Linked arm	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		✓	578	100.000
B		✓	0	100.000
C		✓	537	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
From		A	B	C
	A	0	35	543
	B	0	0	0
	C	502	35	0

Vehicle Mix

Heavy Vehicle Percentages

	To			
From		A	B	C
	A	10	10	10
	B	10	10	10
	C	10	10	10

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS
B-AC	0.00	0.00	0.0	A
C-AB	0.07	7.23	0.1	A
C-A				
A-B				
A-C				