


FULL  PRODUCTION



TREETOP ADVENTURE GOLF MANCHESTER PRINTWORKS

SHOP FRONT TECHNICAL TREATMENT BY FULL PRODUCTION

GENERAL AREAS

NOTES

Prepared by Steve Richardson.

Drawing is not a construction drawing and is purely for illustrative purposes.

Internally lit signage (provided by others?) to have additional data for possible future expansion / conversion to digital display.

Outdoor RGB fixture uplighting signing from beneath. Fixtures to be placed behind front lip so as to mask from view.



Indoor rated screen to be placed up against the glass.

NO.	REVISION / ISSUE	DATE
3		
2	2.1	22/09/2022
1	1.1	21/01/2022

PROJECT NAME AND ADDRESS

Treetop Adventure Golf
Printworks
Manchester

PROJECT
Manchester Shopfront
Technical Treatment

DATE
22/9/2022

SCALE
NTS

SHEET
TTAG/MAN/SF/1

Shopfront

TECHNICAL SPECIFICATIONS

Signage Lighting

Standard Product Versions



Key Features

Low profile, high output, wide range of optics, easy to connect, IP67

Lumen Output & Light Source (version 1/2/3/4)
Max. 1147/2294/3441/4588 lm
12/24/36/48 x Single Chip

Projected Lumen Maintenance
60,000 hrs (L70@25°C)

Power Consumption (version 1/2/3/4)
Typ. 25/45/65/85W

Physical (max HxWxL version 1/2/3/4)
107 x 76 x 329/629/929/1229mm - 2.5/4.2/5.9/7.7kg
3.6 x 3.0 x 13.0/24.8/36.6/48.4in. - 5.5/9.25/13/16lbs
Aluminium Body, Tempered Glass

Width x Height x Length	Eminere 1		76 x 107 x 329 mm (2.99 x 3.58 x 12.95 in.)	
	Eminere 2		76 x 107 x 629 mm (2.99 x 3.58 x 24.76 in.)	
	Eminere 3		76 x 107 x 929 mm (2.99 x 3.58 x 36.57 in.)	
	Eminere 4		76 x 107 x 1229 mm (2.99 x 3.58 x 48.38 in.)	
Weight	2.5 kg 5.5 lbs	4.0 kg 8.82 lbs	6.02 kg 13.27 lbs	7.7 kg 17.0 lbs
Housing	High Pressure Extruded Aluminium Body End Caps - Die-Cast Aluminium Tempered Glass			
Finish Options	Standard Colour		Graphite Black (RAL 9011) Silver (RAL 9006)	
	Cost Option		Custom RAL Harsh Environment (RAL 9016, RAL 9011)	
Cables / Connections	IP67 Hybrid Connection (Power + Data)			
Mounting Method	Surface Mount With Different Type of Brackets			
Adjustability	+/- 95°			
Protection Factor	IP67 / Suitable For Wet Locations			
IK Rating	IK06			
Cooling System	Convection			
Operating Ambient Temperature	-20 °C / +40 °C (-4 °F / +104 °F)			
Operating Temperature	+67 °C @ Ambient +40 °C (+153 °F @ Ambient +104 °F)			
Listings	ETL / cETL, CE, RoHS			

Estimated lux level: 3000 lumen

FULL PRODUCTION

NOTES

Prepared by Steve Richardson.

Drawing is not a construction drawing and is purely for illustrative purposes.

3		
2	2.1	22/09/2022
1	1.1	21/01/2022
NO.	REVISION / ISSUE	DATE

PROJECT NAME AND ADDRESS

Treetop Adventure Golf
Printworks
Manchester

PROJECT
Manchester Shopfront
Technical Treatment

DATE
22/09/2022

SCALE
NTS

SHEET
TTAG/MAN/SF/3

Shopfront

POWER AND DATA REQUIREMENTS

Rough DATA and Power requirements.
Illustrative only. A more exact plan to be produced once design agreed and costed

NOTES

Prepared by Steve Richardson.

Drawing is not a construction drawing and is purely for illustrative purposes.

1 x CAT6
1 x 230/240v mains
for signage

2 x CAT6
1 x 230/240v mains
at high level above screen



NO.	REVISION / ISSUE	DATE
3		
2	2.1	22/09/2022
1	1.1	21/01/2022

PROJECT NAME AND ADDRESS
Treetop Adventure Golf
Printworks
Manchester

PROJECT
Manchester Shopfront
Technical Treatment

DATE
22/09/2022

SCALE
NTS

SHEET
TTAG/MAN/SF/4

Shopfront