

GENERAL

CONTRACTORS TO ACCURATELY MEASURE DIMENSIONS & LEVELS ON SITE IN ORDER TO ACHIEVE A SATISFACTORY FIT OF GATES, FENCING & STEPPING PRIOR TO CONSTRUCTION.

TIMBER

ALL TIMBER TO BE HARDWOOD. SOFTWOOD IS ACCEPTABLE IF PRESSURE PRESERVATIVE TREATED OR TANALISED TO BS 5589 SECTION 6. ALL TIMBER TO BE FSC CERTIFIED. CONTRACTOR TO ISSUE CERTIFICATE OF TREATMENT AND FSC CERTIFICATE TO THE CLIENT.

INSTALLATION

ALL FENCING TO BE INSTALLED TO BS1722-PART 5:2006 FOR CLOSE BOARDED AND WOODEN PALISADE FENCING

FENCE FRAME & INFILL PALES

SAWN TIMBER - TOP AND BOTTOM RAIL 2300mm (VARIABLE LENGTH) x 100 x 38mm. FIXED TO POSTS WITH GALVANISED BRACKETS.

VERTICAL PALES TO BE 100 x 38mm BOARDS SUPPORTED WITH INTERMEDIATE RAILS 100 x 38mm.

TIMBER CAPPING - 2300mm LONG x 65 x 38mm

FOR PALISADE; VERTICAL PALES TO BE 75 x 20mm BOARDS SUPPORTED WITH TOP & BOTTOM RAIL 75 x 20mm

TIMBER POSTS

2400mm HIGH x 100mm WIDE x 100mm WIDE (1.8m FENCE)

1600mm HIGH x 100mm WIDE x 100mm WIDE (1.0m FENCE)

ALL CUTS TO BE TREATED WITH PRESERVATIVE PRIOR TO INSTALLATION.

TIMBER GRAVEL BOARD

2300mm LONG x 150mm HIGH x 38mm WIDE

GATES

GATES TO BE CONSTRUCTED AND FIXED WITH SAME MATERIALS AND SIZES AS FENCING

POST FOUNDATION

500 x 450 x 450 mm CONCRETE






500 X 300 x 300mm CONCRETE

TIMBER STAIN

FOR SOFTWOOD ONLY:APPLY 2NR COATS OF JOTUN DEMIDEKK OPAQUE WOODSTAIN. COLOUR 9095 MAHOGANY. APPLY IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS. CONTRACTOR TO ENSURE TIMBER MOISTURE CONTENT 20% PRIOR TO APPLICATION.

FIXINGS

ALL FENCING TO BE HAND NAILED OR SCREWED TOGETHER. ALL METAL FIXINGS TO BE SHERARDIZED OR GALVANISED.



- CLIENT
MAKKI MASJID TRUST

- PROJECT NAME
THE NEW MAKKI MASJID
125 BERESFORD ROAD
MANCHESTER M13 0TA

- DRAWING TITLE
- SITE EXTERNAL WORKS
ENCLOSURES

- DRAWN / CHECKED
AS/GWC

- PROJECT
218-185

- SCALE
1:100 @ A1

- DATE
JAN 2021

- DRAWING No
EW04

- REV.
A