




- BOUNDARIES**
- Site Boundary (planning)
- HARDWORKS**
- K1**
Yorkstone Road Kerb
Location: to Corporation Street
Material: 'Scoutmoor' Yorkstone by Marshalls
Finish: Diamond Sawn. Colour: Grey / Buff
Unit size: 300mm (w) x 900mm (l) x 150/250mm (d)
Notes: 125mm upstand, flush at pedestrian crossing and service bays. Spec to match opposing side of Corporation Street
- K2**
Granite Road Kerb
Location: to Corporation Street
Material: Granite by Hardscape
Finish: Bush Hammered. Colour: 'Kobra'
Unit size: 300mm (w) x 900mm (l) x 150/250mm (d)
Notes: Nominal 60mm upstand to parking bay traffic barrier. Flush to Car Park entrance. Spec to match opposing side of Corporation Street
- K3**
Textured Concrete Kerb
Location: to Car Park
Material: Conservation Kerb by Marshalls
Colour: Silver Grey
Unit size: 145mm (w) x 900mm (l) x 255mm (d)
Notes: 125mm upstand
- P1**
Yorkstone Flag Paving
Location: east of proposed building, to public footpath on Corporation Street
Material: 'Scoutmoor' Yorkstone by Marshalls
Finish: Diamond Sawn. Colour: 50% Grey / 50% Buff
Unit size: 600mm (w) x 400-600mm (l) x 75mm (d)
Laying: Staggered joints
Notes: Suitable for occasional vehicular overrun.
- P2**
Yorkstone Sett Paving
Location: service bay on Corporation Street
Material: 'Scoutmoor' Yorkstone by Marshalls
Finish: Diamond Sawn. Colour: 50% Grey / 50% Buff
Unit size: 140mm (w) x 140-280mm (l) x 75mm (d)
Laying: Staggered joints
Notes: Suitable for HGV overrun
- P3**
Granite Sett Paving
Location: vehicular access route to lower car park.
Material: Granite by Hardscape.
Finish: Bush Hammered top, sawn sides and bottom.
Colour: 50% 'Kobra Green' and 50% 'Kobra'
Unit size: 140mm (w) x 140-280mm (l) x 75mm (d)
Laying: Stretcher bond
Notes: Suitable for vehicular overrun. Contrasting to surrounding Yorkstone.
- P4**
Exposed Aggregate Pre-cast Block Paving
Location: to car park
Material: Kellen Breccia by Hardscape
Colour: Tagenta E (with Tagenta D double header)
Unit size: 200mm (w) x 300mm (l) x 80mm (d)
Laying: Stretcher Bond
Notes: Suitable for vehicular overrun.
- P5**
Exposed Aggregate Pre-cast Block Paving
Location: to car park pedestrian areas
Material: Kellen Breccia by Hardscape
Colour: Tagenta E
Unit size: 200mm (w) x 300mm (l) x 80mm (d)
Laying: Stretcher Bond
Notes: Suitable for vehicular overrun.
- P6**
Corduroy Paving
Location: to top and bottom of steps
Material: Granite by Hardscape
Colour: 'Kobra' Finish: Flamed.
Unit size: 400mm (w) x 400mm (l) x 50mm (d)
Laying: Stack bond
- P7**
Blister Paving
Location: to uncontrolled pedestrian crossings.
Material: Granite by Hardscape
Colour: 'Kobra' (LRV contrast tbc by supplier)
Finish: Flamed.
Unit size: 400mm (w) x 400mm (l) x 50mm (d)
Laying: Stack bond
- P8**
Blister Paving
Location: to controlled pedestrian crossings.
Material: Granite by Hardscape
Colour: 'Imbabwe Red' Finish: Flamed
Unit size: 400mm (w) x 400mm (l) x 50mm (d)
Laying: Stack bond
- P9**
Gravel Maintenance Path
Location: west of Building 1
Material: Loose Grey Limestone Aggregate by CED
Unit size: 20mm
Laying: 50mm deep
- P10**
Car Park Surfacing
Hot rolled asphalt to engineer's specification
- P11**
Vehicle Ramp
Surface to vehicle access ramps to engineer's specification
- P12**
Temporary Car Park Surfacing
Hot rolled asphalt to engineer's specification
- P13**
Paving Demarcation Studs, Stainless Steel
Denoting line of adaptation. Final adoption of line TBC.
Dimensions: 25mm diameter, circular surface textured, at 1m intervals.
Supplier: Urban Finish, tel. 0843 289 4852, or equal and approved.
- WALLING / STEPS KEY**
- Solid Stone Step Units**
Location: To meet public footpath on Corporation Street and pedestrian access to Victoria Station
Material: 'Scoutmoor' Yorkstone by Marshalls
Finish: Diamond Sawn.
50mm width granite contrasting nosing (LRV contrast to be confirmed by supplier)
Unit size: 330mm (tread) x 160mm (riser) x length varies to include pencil round nose radius to step nosing and exposed ends
- Granite Clad Walls**
Location: East of proposed building, to public footpath on Corporation Street
Material: Granite by Hardscape
Colour: 'Kobra'
Finishes: Coping - Cropped, Sides - Flamed.
Unit size: Facing panel - height varies to suit levels x 30mm (d) x length varies. Coping stone - 300-600mm (w) x 80mm (d) x length varies.
Notes: Anti-Skate notches 40 x 20 x 35mm cut into coping units where joints meet. Mechanical fixing to engineer's spec. Refer to details for seating wall spec.
- Granite Clad Planter & Seating**
Location: East of proposed building, to public footpath on Corporation Street
Material: Granite by Hardscape
Colour: 'Kobra'
Finishes: Coping - Cropped, Sides - Flamed.
Overall Sizes (unit sizes vary)
Coping Units - 300/600mm (w) x 150mm (d) x 800mm (l)
Side panels - 350-850mm (h) x 300mm (w) x 30mm (d)
See Detail Sheet PL1487.D.004 for more information
Notes: Anti-Skate notches 40 x 20 x 35mm cut into coping units where joints meet. Mechanical fixing to engineer's spec. Refer to details for seating wall spec.
- Proposed Brick Wall**
New brick wall parapet on existing brick retaining wall leading to Cheltenham Hill Road bridge. Refer to Arup details



Revisions:
Material specifications updated



- NOTE:
- Do not scale from this drawing
 - All setting out, levels and dimensions to be agreed on site.
 - The dimensions of all materials must be checked on site before being laid out.
 - This drawing must be read with the relevant specification clauses and detail drawings
 - Order of construction and setting out to be agreed on site.
 - This drawing is copyright protected and may not be reproduced in whole or part without written authority.
 - All Dimensions are in millimetres unless Otherwise Stated

Planit - IE Limited
2 Back Grafton St. Altrincham WA14 1DY
0161 928 9281

Project **NEW VICTORIA**

Client **Muse Developments**

Drg title **Hardworks Lower GA**

Drg nr **PL1487.VW.114**

Scale **1:250@A1** Date: **24/02/16** Drawn **TF**

Status **Planning** Revision **15.1** Checked **AM**