



Installation Method



Ashlar



Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product	Textured Woodgrains	Colour	Distressed Hickory	Collection	Level Set Collection
Product Specifications					
Product Number	A004				
Product Construction	High Performance Luxury Vinyl Tile contains 39% Pre-Consumer Recycled Content				
Finish	Ceramor™ UV stabilised Ceramic Bead Coating				
Wear Layer Thickness	(EN ISO 24340) 0.55 mm				
Total Thickness	(EN ISO 24346) 4.5 mm				
Total Weight	6,320 g/m²				
Size	25cm x 1m				
Tiles per Box	10 - 2.5m²				
Backing	Sound Choice+™ Acoustic Backing				
Performance Specifications					
Wear Classification	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial				
CE Declaration Of Performance	MOC2024-0087				
UKCA Declaration of Performance	MOC2024-0087				
Castor Chair Rating	(ISO 4918 / EN425) Pass				
Flammability	(EN ISO 9239-1: 2010) Euroclass Bfl-s1 (EN 13501-1)				
Light Fastness	≥6 (ISO 105-B02)				
Light Reflectance Value (LRV-L)	53.93				
Light Reflectance Value (LRV-Y)	21.91				
Curling	≤ 2 mm (ISO 23999)				
Residual Indentation	≤0.2mm				
Determination of Anti-Slip	R9 (DIN 51130)				
Pendulum Dry 45	36+ (BS 7976-2) Low slip potential				
Chemical Resistance	(EN ISO 26987) Very Good				
Impact Sound Insulation ΔLw EN ISO 10140-3	Upto 19 dB				
Environmental Specifications					
Environmental Product Declaration	Download EPD				
Disclosure of Product Ingredients	Health Product Declaration				
Total Recycled Content	39 %				
Indoor Air Quality	French A+ Indoor Air Comfort GOLD® LVT Greenguard Gold M1 Emission Certification - LVT FloorScore® SCS-FS-04366				
Embodied Carbon (Cradle to Gate)	6.8 kg CO ₂ eq./m²				
End of Life Options	Fully Recyclable: Can be recycled into carpet tile backing. ReUse: Can be cleaned and reused in a non-critical location to extend its useful life.				
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.				
Fully Recyclable	Can be recycled into carpet tile backing.				
Material Composition	Free of Ortho Phthalates				
Technical Information					
Installation	See recommended LVT installation guidelines				
Maintenance	See recommended LVT maintenance guidelines				
Warranty	15 years LVT				

Certifications

