

		Axial					Shear
Pile Ref	Pile Dia (mm)	Dead (kN)	Imposed (kN)	Wind Comp. (kN)	Wind Tens. (kN)	Wind (kN)	
P101	750	825	80	205	-430	50	
P102	750	1190	140	250	-420	50	
P103	750	1455	180	285	-405	50	
P104	750	1555	200	305	-355	50	
P105	750	1490	195	350	-345	50	
P106	750	1275	165	375	-325	50	
P107	750	960	120	440	-370	50	
P108	750	595	65	525	-405	50	
P109	750	1145	140	565	-435	50	
P110	750	1525	195	465	-395	50	
P111	750	1845	240	395	-355	50	
P112	750	2005	260	345	-365	50	
P113	750	2005	255	315	-425	50	
P114	750	1825	225	280	-475	50	
P115	750	1460	165	235	-500	50	
P116	750	1035	95	240	-555	50	
P117	750	1665	180	280	-635	50	
P118	750	2130	255	270	-580	50	
P119	750	2440	305	315	-515	50	
P120	750	2480	320	335	-405	50	
P121	750	2390	315	405	-375	50	
P122	750	2110	275	495	-425	50	
P123	750	1700	215	605	-470	50	
P124	750	1275	155	695	-505	50	
P125	750	1760	225	725	-520	50	
P126	750	2240	290	640	-495	50	
P127	750	2630	345	485	-420	50	
P128	750	2810	360	355	-360	50	
P129	750	2905	365	320	-485	50	
P130	750	2825	345	300	-670	50	
P131	750	2315	270	330	-730	50	
P132	750	1745	185	360	-740	50	
P133	750	2285	260	410	-800	50	
P134	750	2960	355	400	-835	50	
P135	750	3050	380	230	-520	50	
P136	750	3055	390	230	-290	50	
P137	750	2895	375	340	-300	50	
P138	750	2645	345	605	-450	50	
P139	750	2180	280	715	-495	50	
P140	750	1710	215	810	-540	50	
P141	750	2025	260	760	-480	50	
P142	750	2495	325	650	-420	50	
P143	750	2845	370	445	-300	50	
P144	750	3060	395	150	-130	50	
P145	750	3230	405	110	-260	50	
P146	750	3220	395	380	-710	50	
P147	750	2765	325	450	-815	50	
P148	750	2120	230	460	-810	50	
P149	750	2470	280	500	-800	50	
P150	750	3130	380	500	-805	50	
P151	750	3165	395	280	-435	50	
P152	750	3165	405	60	-70	50	
P153	750	2985	390	295	-150	50	
P154	750	2730	360	565	-315	50	
P155	750	2275	295	705	-405	50	
P156	750	1800	230	810	-470	50	
P157	750	1960	250	770	-405	50	
P158	750	2450	320	675	-335	50	
P159	750	2820	370	485	-210	50	
P160	750	3035	395	265	-185	50	
P161	750	3175	405	265	-300	50	
P162	750	3065	380	485	-670	50	
P163	750	2705	320	550	-805	50	
P164	750	2105	230	550	-825	50	
P165	750	2195	250	555	-770	50	
P166	750	2765	335	560	-735	50	
P167	750	2975	375	425	-495	50	
P168	750	2935	380	335	-320	50	
P169	750	2800	370	445	-280	50	
P170	750	2520	330	600	-245	50	
P171	750	2030	265	700	-330	50	
P172	750	1560	195	785	-400	50	
P173	750	1530	190	685	-315	50	
P174	750	1980	255	595	-255	50	
P175	750	2370	310	520	-310	50	
P176	750	2555	335	420	-340	50	
P177	750	2600	335	385	-410	50	
P178	750	2465	305	455	-530	50	
P179	750	2095	245	510	-655	50	
P180	750	1630	175	535	-720	50	
P181	750	1450	160	470	-590	50	
P182	750	1820	215	430	-495	50	
P183	750	2075	260	385	-425	50	
P184	750	2130	275	390	-360	50	
P185	750	2040	265	465	-335	50	
P186	750	1775	230	510	-295	50	
P187	750	1400	175	570	-245	50	
P188	750	995	115	660	-300	50	
P189	750	840	95	550	-235	50	
P190	750	1200	145	495	-285	50	
P191	750	1485	190	475	-325	50	
P192	750	1640	210	420	-345	50	
P193	750	1640	205	390	-380	50	
P194	750	1485	180	370	-415	50	
P195	750	1195	130	395	-455	50	
P196	750	825	75	430	-530	50	

		Axial				Shear
Pile Ref	Pile Dia (mm)	Dead (kN)	Imposed (kN)	Wind Comp. (kN)	Wind Tens. (kN)	Wind (kN)
P501	500	220	25	5	-10	10
P502	500	875	170	5	0	30
P503	750	1640	340	0	-5	50
P504A	500	1315	240	5	-10	35
P504B	500	625	85	15	-10	35
P505	750	2465	370	215	-180	40
P506	750	2305	340	195	-115	40
P507	750	2815	440	130	-245	40
P508	750	2815	445	30	-40	40
P509	750	3520	610	200	-135	50
P510	750	3025	525	5	-5	50
P511	750	3550	620	100	-200	50
P512	750	3840	680	190	-130	50
P513	750	3410	570	0	-5	50
P514	750	3880	675	105	-210	50
P515	750	3675	625	45	-50	40
P516	750	3790	635	20	-30	40
P517	500	475	85	15	-30	30
P518	750	2900	470	60	-110	40
P519	750	2980	485	20	-45	40
P520	750	3610	615	55	-45	50
P521	750	3105	525	235	-135	50
P522	750	3585	615	105	-50	50
P523	750	3000	515	20	-35	50
P524	750	2610	455	125	-215	50
P525	750	3005	520	15	-25	50
P526A	500	230	90	5	-10	30
P526B	500	250	30	10	-25	30
P527	750	2930	510	110	-210	40
P528	750	3030	515	50	-100	40
P529	750	2840	490	95	-70	40
P530	750	2765	475	215	-140	40
P531	750	2795	470	215	-115	40
P532	750	2900	480	100	-50	40
P533	750	3070	525	70	-100	40
P534	750	3015	520	135	-205	40
P536	500	600	115	10	-15	30
P537	750	2605	445	130	-200	50
P538	750	2895	500	25	-40	50
P539	750	2880	495	50	-60	50
P540	750	2760	450	40	-25	50
P541	750	2315	395	195	-110	50
P542	750	2680	445	65	-30	50
P543	750	2750	440	120	-65	40
P544	750	2745	440	70	-35	40
P545	750	2875	465	75	-110	40
P546	750	2875	465	40	-55	40
P547A	500	325	35	5	-5	30
P547B	500	730	135	85	-155	30
P548	750	3175	555	20	-25	40
P549	750	3140	540	50	-55	40
P550	750	3270	550	75	-85	50
P551	750	3000	490	10	-5	50
P552	750	3275	540	110	-50	50
P553	750	3385	550	80	-90	50
P554	750	3040	490	10	-5	50
P555	750	3310	550	110	-50	50
P556	750	3615	585	55	-65	40
P557	750	3575	580	85	-35	40
P558	500	220	35	5	-15	30
P559	500	395	100	15	-35	30
P561	750	1945	250	150	-260	40
P563	750	1840	300	70	-115	45
P564	750	1800	290	70	-35	45
P565	750	1795	165	230	-120	45
P566	500	805	120	210	-115	35