

Quick... Discrete...

number; the Link Vent Mk2 now comes in 1,000's of colour options. You can even mix and match when your customers select window designs with colour foiled profile externally and white internally.

But how could we improve the product even more if you're an installer or fabricator? There are still NO end caps to loose or break... fixing is within the products design. The Link vent Mk2 is supplied with fixing clips fitted! So, you can just push fit the vent into place when installing...in seconds. The clips automatically centre the vent in the rout aiding location ensuring it is fitted level on the window.

IF you still prefer to screw fix your trickle vents, just pop out the fitted screw caps before fitting and fix as normal.

LINKVENT Mk II 5000

5000 VENT

Equivalent Area 5000mm ² EQA	Free Area 5049mm ²	Acoustic D n,e,w (+/-) - vent open 35(0;1)	Acoustic D n,e,w (+/-) - vent closed 43(0;0)
--	----------------------------------	---	---

Internal				External								Ventilator			
Ventilator				Canopy				Grille (Timber, Sliding door, Sash)							
H (mm)	L (mm)	D (mm)	Weight (gram)	H (mm)	L (mm)	D (mm)	Weight (gram)	H (mm)	L (mm)	D (mm)	Weight (gram)	Attachment type	Rout H (mm)	Rout L (mm)	Stand W (mm)
18.5	454.5	15	60	18.5	454.5	25	49	26	436	2.5	20	Clip or Screw	13	422	14

EQUIVALENT AREA – 5000 vent (5000EQA)

AIR LEAKAGE – 5000 vent 1.29 m³/h 0.36 L/s

WATERTIGHTNESS TEST TO BS EN 13141-1 – 5000 vent – Resistant to water penetration using method 1A meeting Class 9A requirement up to and at 600pa in BS EN 12208

DB RATING – Airbourne sound insulation to BS EN ISO 10140-1:2016 Annex E and BS EN ISO 10140-2:2010 and single number calculated in accordance with BS EN ISO 717-1:2013

