PROJECT
Manchester Office Relocation - Pall Mall

CLIENT
Sheppard Robson LLP

DESCRIPTION
Internal Wall Finishes Types Schedule

STAGE
Stage 4

SR NO.	SCALE@A3	DATE
10157	**1 : 200**	**17/04/2026**
ORIGINATOR	CHECKED	AUTHORISED
AB	**ML**	**ML**

REVISIONS

REV.	DATE	AMENDMENT
P01	05/01/2026	First Issue
P02	30/03/2026	Stage 4 Issue
P03	17/04/2026	Updated and issued as part of Listed Building Consent

NOTES
- Allow for all walls to be WF61 General Paint unless otherwise noted.
- Assume all finishes are full height unless otherwise stated, refer to wall finish elevations for more detail

WALL FINISH CODES:
- WF01-10 Sheet Products
- WF11-20 Glazed Finishes
- WF21-30 Timber Products
- WF31-40 Stone/Ceramics
- WF41-50 Metal Surfaces
- WF51-60 Other Surfaces
- WF61-80 Painting & Decorating
- WF81-90 Basebuild/Existing

ID:SR
E: enquiries@sheppardrobson.com

A3

REV.	STATUS	PURPOSE FOR ISSUE
P03	**S2**	**Planning**

DRAWING NO.
10157-IDSR-XX-ZZ-SH-I-42900

Code	Description	Manufacturer	Range	Finish	Colour	Size	Acoustic Rating	Fire Rating	Notes
WF11A	Writeable Surface	Lintex	Mood Wall	Matt	Pure 130	Refer to 42200/400 series	n/a	n/a	Bespoke Sizes. For setting out refer to 42400 series wall elevations.
WF12A	Writeable Surface	Lintex	Air Spaces	Matt	White	Refer to 42200/400 series	n/a	n/a	Standard sizes. Refer to 42400 Series for dimensions and setting out. Air Texture panel included
WF31A	Ceramic Tile	Domus	TBride	Glossy	DTTB02	160 x 52 x 10mm	n/a	n/a	Refer to 4200/400 series.Contractor to ensure seamless istallation. Grout colour tbc. ile setting out to be coordinated with specialist joinery ensure no cut tiles
WF32A	Ceramic Tile	Johnson Tiles	Prismatics	Glossy	White PRG 1	100mm x 100mm	n/a	n/a	Grout colour to match tile (tbc subject to sample review). Allow for stainless steel angle trim to all exposed edges. No cut tiles permitted
WF51A	Acoustic Ribbed Wall Panel	Autex	Groove VI 60 degree angle	PET	Opera	12mm depth	NRC 0.45	BS EN 12301 - 1:2018 B-s2, d0	For sizing & setting out, refer to 42401 for wall elevations.
WF52A	Acoustic Wall Panel	Autex	Cube	-	Opera	12mm depth	NRC 0.45	BS EN 13501- 1:2018 B-s2, d0	<varies>
WF53A	Pinnable Wall Surface	Lintex	Air Noticeboard	Cork	Cork	22mm Thick	n/a	n/a	For sizing & setting out, refer to 20403 wall elevations. Allow for a stainless steel angle trim to all exposed edges

Code	Description	Manufacturer	Range	Finish	Colour	Size	Notes
60 [Paint Finishes]							
WF61A	Paint Type 01A (General Paint)	Dulux Trade	Airsure Vinyl Matt	Matt	TBC (Off-White)	Refer to 42200 series	Number of coats, including any primer coats strictly in line with the manufacturers recommendations.
WF61B	Paint Type 01B (High Level)	Dulux Trade	Airsure Vinyl Matt	Matt	TBC (Off-Black)	Refer to 42200 series	Number of coats, including any primer coats strictly in line with the manufacturers recommendations.
WF61C	Paint Type 01C (Feature)	Dulux Trade	Airsure Vinyl Matt	Matt	TBC (Colour)	Refer to 42200 series	Number of coats, including any primer coats strictly in line with the manufacturers recommendations.

Code	Description	Manufacturer	Finish	Colour	Size	Notes
SK [Skirting]						
SK01A	Plant on Skirting throughout unless indicated otherwise	By Specialist Joiner	12mm MDF Painted, Matt	To match adjacent wall finish	Refer to 42200/400 series	Height to match existing X 12mm depth
SK02A	Recessed Skirting	By Joiner	12mm MDF Painted, Matt	To match adjacent wall finish	Refer to 42200/400 series	Where recessed skirting is specified, contractor to ensure that suitable partition build up is provided to comply with fire & acoustic requirements. 100mm high skirting to align with adjacent joinery units. All timber to recieve Dulux Trade Diamond Satinwood, whereno specialist finish is specefied.

© COPYRIGHT
The copyright in this drawing is vested in ID:SR and no license or assignment of any kind has been, or is, granted to any third party whether by provision of copies or originals or otherwise unless agreed in writing.

DO NOT SCALE FROM THIS DRAWING
The contractor shall check and verify all dimensions on site and report any discrepancies in writing to ID:SR before proceeding work

FOR ELECTRONIC DATA ISSUE
Electronic Data / drawings are issued as "read only" and should not be interrogated for measurement. All dimensions and levels should read, only from those values stated in text on the drawing.