PROJECT
Manchester Office Relocation - Pall Mall

CLIENT
Sheppard Robson LLP

DESCRIPTION
Floor Finishes Types Schedule

STAGE
Stage 4

SR NO.	SCALE@A3	DATE
10157	**1 : 200**	**17/04/2026**

ORIGINATOR	CHECKED	AUTHORISED
OSW	**ML**	**ML**

REVISIONS

REV.	DATE	AMENDMENT
P01	05/01/2026	First Issue
P02	30/03/2026	Stage 4 Issue
P03	17/04/2026	Updated and issued as part of Listed Building Consent

NOTES
•Contractor to ensure all finishes are installed flush/levelled.
•All finishes to sit tightly against each other with no trim. Should a trim be required, allow for a metal "L" profile trim in stainless steel.

FLOOR FINISH CODES:
- FL01-10 Carpet Products
- FL11-20 Timber Products
- FL21-30 Resilient Flooring
- FL31-40 Stone/Ceramics
- FL41-50 In-Situ
- FL51-60 Matting
- FL61-70 Resin/Paints
- FL71-80 Inset Rugs
- FL81-90 Basebuild/Existing

ID:SR
A3
E: enquiries@sheppardrobson.com

REV.	STATUS	PURPOSE FOR ISSUE
P03	**S2**	**Planning**

DRAWING NO.
10157-IDSR-XX-ZZ-SH-I-43900

Code	Description	Manufacturer	Range	Finish	Colour	Size	Accessibility	Notes
01 [Carpet Systems]								
FL01A	Carpet Tile	Interface	Connect, CE100	Tufted Patterned Structured Loop Pile	4314001	500mm x 500mm	Accessible	To be installed in a non-directional layout. Allow for stainless steel angle trim if/where required. Contractor to review all floor build ups to ensure flush and step free surfaces throughout.
FL02A	Carpet Tile	Interface	City of Angels	Tapestry Tufted Patterned Structured Loop Pile	8130002	500mm x 500mm	Accessible	To be installed in a Monolithic layout. Allow for stainless steel angle trim between finishes if/where required. Contractor to review all floor build ups to ensure flush and step free surfaces throughout.
10 [Timber Products]								
FL11A	Engineered Timber Floor	Domus	Robur 240	Extra Matt UV Lacquer	WDRO 002	240mm x 2200mm	Inaccessible	Contractor to allow for expansion trims, 8mm minimum to the perimeter of the timber, to befully concealed beneath the skirtings. Raised access floor to be lowered to achieve level floor finish throughout. RAF pedestals mechanically fixed & panels screwed to pedestals. RAF panels are to be degreased & lightly abrased. Timber floor to be floating with 'Silent Walk' underlay, 2mm thick.
20 [Resilient Flooring]								
FL21A	Woven Vinyl - Sheet	Bolon	Elements	-	Cork	Roll - 2000mm x 25m (2.4mm thickness)	Inaccessible	Ensure a seamless and fully levelled finish. Final build up to be confirmed by flooring contractor, however suitable ply underlay to be allowed for, strictly in line with the manufacturers recommendations. Allow for stainless steel angle abutment trim.
FL22A	Marmoleum Lino Sheet	Forbo	Marmoleum Solid - Cocoa	-	3590 Meringue	Roll- 2000mm x 33m (2.5mm thickness)	Inaccessible	Suitable build up to be allowed for to ensure fully levelled surface. Allow for stainless steel angle trim to all floor abutment areas. Positon of seamless joints to be agreed before installation
FL23A	Safety Floor	Forbo	Surestep	-	Original 172312	Roll- 2000mm x 33m (2.5mm thickness)	Inaccessible	Suitable build up to be allowed for to ensure fully levelled surface. Allow for stainless steel angle trim to all floor abutment areas.
FL24A	Anti-Static Vinyl	Interface	Noraplan Sentica	-	6505	Tile- 610mm x 610mm	Accessible	
70 [Rugs]								
FL71A	Loose lay rug	Kasthall	Arkad	Pattern: 932	134804-10	4500mm x 2900mm	Accessible	Allowance for 1 no. custom cut out for floor box, finished edge required
FL71B	Loose lay rug	Kasthall	Arkad	Pattern: 932	134804-10	2700mm x 2300mm	Accessible	
FL72A	Loose lay rug	Kavadrat	Braid.2	Polyester	TBC	2200mm x 4000mm	Accessible	Allowance for 1 no. custom cut out for floor box, finished edge required.

© COPYRIGHT
The copyright in this drawing is vested in ID:SR and no license or assignment of any kind has been, or is, granted to any third party whether by provision of copies or originals or otherwise unless agreed in writing.

DO NOT SCALE FROM THIS DRAWING
The contractor shall check and verify all dimensions on site and report any discrepancies in writing to ID:SR before proceeding work

FOR ELECTRONIC DATA ISSUE
Electronic Data / drawings are issued as "read only" and should not be interrogated for measurement. All dimensions and levels should read, only from those values stated in text on the drawing.