Specifications Table for 3MXM-M

					3MXM40M2V1B	3MXM52M2V1B	3MXM68M2V1B
Fan	Air flow rate	Cooling	Super low	m^3/min	24	24	24.1
		Heating	Super low	m^3/min	24	24	24.1
			Super low	cfm	847	847	851
		Heating	Super low	cfm	847	847	851
Dimensions	Unit		Height	mm	734	734	734
			Width	mm	868	868	868
			Depth	mm	320	320	320
Weight	Unit			kg	57	57	62
Fan motor	Speed	Cooling	Super low	rpm	420	420	

		Heating	Super low	rpm	420	420	
Compressor	Type				Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor
Operation range	Cooling	Ambient	Min.	°CDB	-10	-10	-10
			Max.	°CDB	46	46	46
	Heating	Ambient	Min.	°CWB	-15	-15	-15
			Max.	°CWB	18	18	18
Sound pressure level	Cooling		Nom.	dBA	46	46	48
	Heating		Nom.	dBA	47	47	48
Refrigerant	Type				R-32	R-32	R-32
	Charge			kg	1.80	1.80	2.0
	Charge			tCO2Eq	1.2	1.2	1.4
	GWP				675	675	675
Piping connections	Piping length	OU - IU	Max.	m	25	25	25
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 30m)	0.02 (for piping length exceeding 30m)	

	Level difference	IU - OU	Max.	m	15	15	15
		IU - IU	Max.	m	7.5	7.5	7.5
	Total piping length	System	Actual	m	50	50	
Standard Accessories	Installation manual				1	1	1
	Drain plug				1	1	1
	Screw bag				1	1	1
Power supply	Phase				1~	1~	1~
	Frequency			Hz	50	50	50
	Voltage			V	220-240	220-240	220-240
Standard Accessories	Drain cap						9
	Reducer assembly						1