Falcon Wall

Part of the Emergency product category

Model	Falcon Wall Self-Test Emergency Black
Code	AFW/1/B/3NM/ST
Application	Commercial, Education, Healthcare, Hospitality, Outdoor, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	1.3W
Operating Temp	0°C - 40°C
Lumens Delivered	80lm
lm/W	N/A
CCT	6500K
Beam Angle	45/120

MATERIAL INFORMATION

Main Material	Polycarbonate
Product Weight without Packaging	0.2869 kg
Colour / Finish	Black

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	6
CRI	Ra 70
Internal / External	Internal / External
Surface / Recessed / Suspended	Recessed
Power Factor	0.3
L70 @ 25°C	L70 B50 73,000h

PRODUCT FEATURES

- Ultra-low profile recessed or surface mounted emergency low-level light suitable for most internal and external applications
- Cutting-edge lens design maximises light output and performance, allowing increased spacing reducing cost
- Integral IP65 open area lens ideal for external escape route installations
- Low level installations provide the required lux levels on the floor reducing the need for ceiling emergency lighting
- Available in black and white finishes





Falcon Wall

Part of the Emergency product category

Model	Falcon Wall Self-Test Emergency Black
Code	AFW/1/B/3NM/ST
Application	Commercial, Education, Healthcare, Hospitality, Outdoor, Retail







